

PMA TRUST & system supports

Introduction

For flexible and application friendly solutions. PMA offers a vast array of practical accessories in order to complete the PMA cable protection system.

We offer lock nuts produced from polyamide or metal, thread reducers and enlargers, conduit adapters, swivel adapters as well as different mounting clips for conduits. All these practical products will help to create the PMA line for our customers even more flexible and application friendly.





PMA TRUST™

Modular support system

For use in rolling stock applications.
The most versatile, compact and lightest design of its kind on the market.



PMA® TRUST™ modular support system is a lightweight, compact solution with high impact resistance. Thanks to the new design, external dimensions are reduced to the very minimum and internal spacing between adjoining conduits is very small. The system is specifically designed for use in railway vehicle construction and other applications where fixation of parallel running conduits and cables is required.

Type BGPM - PMA TRUST™ modular support system

	Order no. black	Conduit size NW	No. of conduits	Nom. dimensions (mm)			PU (pcs)
				Length	Depth	Height	
	BGPM-1x10	10	1	39.5	30.0	24.5	10
	BGPM-1x12	12	1	42.5	30.0	28.0	10
	BGPM-2x12	12	2	61.0	30.0	28.0	10
	BGPM-3x12	12	3	79.5	30.0	28.0	5
	BGPM-4x12	12	4	98.0	30.0	28.0	5
	BGPM-1x17	17	1	48.0	30.0	33.0	10
	BGPM-2x17	17	2	72.5	30.0	33.0	10
	BGPM-3x17	17	3	97.0	30.0	33.0	5
	BGPM-4x17	17	4	121.5	30.0	33.0	5
	BGPM-1x23	23	1	55.0	30.0	40.0	10
	BGPM-2x23	23	2	87.0	30.0	40.0	10
	BGPM-3x23	23	3	119.0	30.0	40.0	5
	BGPM-4x23	23	4	151.0	30.0	40.0	5
	BGPM-1x29	29	1	61.0	30.0	46.0	10
	BGPM-2x29	29	2	99.5	30.0	46.0	10
	BGPM-3x29	29	3	137.5	30.0	46.0	5
	BGPM-4x29	29	4	176.0	30.0	46.0	5
	BGPM-1x36	36	1	70.0	30.0	55.0	10
	BGPM-2x36	36	2	116.5	30.0	55.0	10
	BGPM-3x36	36	3	163.0	30.0	55.0	5
	BGPM-4x36	36	4	209.5	30.0	55.0	5
	BGPM-1x48	48	1	82.0	30.0	66.0	10
	BGPM-2x48	48	1	141.0	30.0	66.0	10
	BGPM-3x48	48	3	199.5	30.0	66.0	5
	BGPM-4x48	48	4	258.5	30.0	66.0	5

For applications in rail vehicle construction and other applications where fixation of parallel running conduits and cables is required

Light weight and compact design
Conduit rotation possible preventing torsion
Axial fixation of conduit and/or cables
Quick installation, possible with one hand

PMA TRUST™ modular support system

Type BGPM, BGPMR & BGPMK

Type BGPMR - PMA TRUST™ reducers

	Order no. black	Conduit size NW	Fits to multiple holder BGPM (NW)	Fits to reduction BGPMR	Depth (mm)	PU (pcs)
	BGPMR-10T/17	10	17	17	30.0	5
	BGPMR-12T/17	12	17	17	30.0	5
	BGPMR-17GT/23	17	23	23	30.0	5
	BGPMR-23GT/29	23	29	29	30.0	5
	BGPMR-29GT/36	29	36	36	30.0	5
	BGPMR-36GT/48	36	48	–	30.0	5

Reducers for BGPM modular system support for downsizing corrugated conduits

Provides axial strain relief for conduits, but allows rotation

Combination of multiple reductions possible

Easy installation

Type BGPMK - PMA TRUST™ cable clamping adapter

	Order no. black	Clamping range		Fits to multiple holder BGPM & reduction BGPMR (NW)	Depth (mm)	PU (pcs)
		1 fold BGPM & BGMPR	2, 3 & 4 fold BGPM & BGMPR*			
	BGPMK-10/7-3	7-3	6-4	10	30.0	5
	BGPMK-12/9-5	9-5	8-6	12	30.0	5
	BGPMK-17/15-11	15-11	14-12	17	30.0	5
	BGPMK-17/12-8	12-8	11-9	17	30.0	5
	BGPMK-23/20-16	20-16	19-17	23	30.0	5
	BGPMK-23/18-14	18-14	17-15	23	30.0	5
	BGPMK-29/25-21	25-21	24-22	29	30.0	5
	BGPMK-29/22-18	22-18	21-19	29	30.0	5
	BGPMK-36/34-30	34-30	33-31	36	30.0	5
	BGPMK-36/31-27	31-27	30-28	36	30.0	5
	BGPMK-36/28-24	28-24	27-25	36	30.0	5
	BGPMK-48/46-42	46-42	45-43	48	30.0	5
	BGPMK-48/43-39	43-39	42-40	48	30.0	5
	BGPMK-48/40-36	40-36	39-37	48	30.0	5
	BGPMK-48/37-33	37-33	36-34	48	30.0	5

*We recommend to use cable with the slight reduced clamping range to ensure both optimum cable clamping as well as pre-assembly

Cable clamping adapters for BGPM Multiple Holders and BGPMR reduction half-shells for supporting and holding cables

Provides axial strain relief for cables

Flexible configuration in multiple holders & reductions possible

Easy installation

System supports, half-shells

Type VH & GN

Type VH - System support

	Order no. support ①	Order no. clip ①	Order no. complete ①	Fits to conduit size NW	Width x Height x Depth (mm)	Fixing screws	PU (pcs)
	BVH-17-010	BVH-17-020	BVH-17-000	17	35 x 36 x 36	6 x M5	100
	BVH-23-010	BVH-23-020	BVH-23-000	23	35 x 44 x 36	6 x M5	100
	BVH-29-010	BVH-29-020	BVH-29-000	29	46 x 52 x 40	6 x M5	100
	BVH-36-010	BVH-36-020	BVH-36-000	36	53 x 58 x 60	6 x M5	100
	BVH-48-010	BVH-48-020	BVH-48-000	48	66 x 72 x 60	6 x M5	60

For applications in machine building and installation
 Optimal axial strain relief due to integrated rib
 Variable fixation possible due to six holes, safe against turning
 With safety lid suitable for overhead installation
 High retention forces
 PA 6

Type GN - Half shell

	Order no. fine profile, black	Order no. coarse profile, black	Order no. fine and coarse profile, black	Fits to conduit size NW	Outside Ø (mm)	Width (mm)	PU (pcs)
	BGN-S12T	–	–	12	26.5	34.0	50
	–	–	BGN-S17GT	17	32.0	34.0	50
	BGN-S23T	BGN-S23G	–	23	39.5	34.0	30
	–	–	BGN-S29GT	29	47.0	34.0	30
	–	–	BGN-S36GT	36	55.0	34.0	20
	BGN-S48T	BGN-S48G	–	48	66.5	34.0	20
	–	BGN-S70G	–	70	93.5	38.0	10

For conduit fixation in conjunction with beam systems, particularly in traction and machine applications
 Fixes conduit against axial movements
 Allows radial turning of conduit
 Especially suitable for dynamic applications due to rounded edges
 PA 6

① Please replace “B” for black with “S”
 for grey in front of the order no.

System supports, rails for system supports

Type FH-0, FHS & GPS

Type FH-0 - System support, one-piece

	Order no. black	Order no. grey	Fits to conduit size NW	Width x Height x Depth (mm)	Fixing screws	PU (pcs)
	BFH-07-0	SFH-07-0	07	17.0 x 21.5 x 20.0	1 x M4	100
	BFH-10-0	SFH-10-0	10	20.5 x 24.5 x 20.0	1 x M5	100
	BFH-12-0	SFH-12-0	12	24.0 x 27.0 x 20.0	1 x M5	100
	BFH-17-0	SFH-17-0	17	30.0 x 34.0 x 20.0	1 x M6	100
	BFH-23-0	SFH-23-0	23	38.5 x 42.0 x 20.0	1 x M6	100
	BFH-29-0	SFH-29-0	29	45.5 x 48.0 x 20.0	1 x M6	100
	BFH-36-0	SFH-36-0	36	55.5 x 56.0 x 20.0	1 x M6	50
	BFH-48-0	SFH-48-0	48	67.5 x 68.0 x 20.0	1 x M6	20

For applications in machine building and installation
Optimal axial strain relief due to integrated rib
Suitable for overhead installations due to safety lid
High retention forces
Quick mounting due to single hole fixing
Fits to rail for system support FHS
PA 6

Type FHS - Rail for system support

	Order no. black	Order no. grey	Fits to system supports	Length x Height x Depth (mm)	PU (pcs)
	BFHS-00	SFHS-00	FH-NW-0	275.0 x 15.5 x 25.0	10
	Additional position supports or distance spacers				
	BFHS-PH	SFHS-PH	Position support with screws		20
	BFHS-PH1	SFHS-PH1	Distance spacers		100

For flexible assembly of one-piece system supports and/or fixation of various conduit sizes
Glass fibre reinforced polyamide 6
Extremely robust construction
High stiffness
Positioning and distance spacers available
Glass fibre reinforced PA6

Type GPS - System support, one-piece, stackable

	Order no. black	Fits to conduit size NW	Width (mm)	Height (mm)	Depth (mm)	PU (pcs)
	BGPS-12/01*	12	70.0	51.0	30.0	30
	BGPS-17	17	70.0	51.0	30.0	30
	BGPS-23	23	70.0	51.0	30.0	30
	BGPS-29	29	85.0	65.0	30.0	20
	BGPS-36	36	85.0	65.0	30.0	10
	BGPS-48	48	115.0	92.5	30.0	10
	BGPS-56	56	115.0	92.5	30.0	10

* This size will be delivered with a half-shell insert

In railway vehicle construction, heavy machine building industry and other applications with increased mechanical requirements
Heavy design, high retention forces. Applicable with standard metal C rails
Clasp for easy pre-mounting and final assembly. Especially suitable for dyn. applic. due to rounded edges
The following nominal widths can be combined for stacking: NW 12 with NW 17 + 23, NW 17 with NW 23,
NW 29 with NW 36, NW 48 with NW 56
Content of delivery: System support and 2 screws for securing of the lid (optional); without mounting accessories
PA 6

Tube clamps

Type GL & GH

Type GL - Tube clamp, one-piece

	Order no. black	Fits to conduit size NW	Width (mm)	Fixing screws	PU (pcs)
	BGL-07	07	25.0	1 x M4	100
	BGL-10	10	27.0	1 x M4	100
	BGL-12	12	31.0	1 x M4	100
	BGL-17	17	39.5	1 x M5	100
	BGL-23	23	49.0	1 x M5	100
	BGL-29	29	57.0	1 x M6	100

Used in general machine and installation applications
 Integrated rib provides axial strain relief
 Allows turning of the conduit, thus avoiding torsion stresses
 Pre-fixation on the conduit possible
 PA 6

Type GH - Tube clamp, one-piece

	Order no. black	Thread outside NW	Width (mm)	Fixing screws	PU (pcs)
	BGH-23	23	16.0	2 x M5	50
	BGH-29	29	19.0	2 x M6	50
	BGH-36	36	24.0	2 x M6	50
	BGH-48	48	24.0	2 x M6	50
	BGH-56	56	26.0	2 x M8	10
	BGH-70	70	30.0	2 x M8	10
	BGH-95	95	30.0	2 x M8	10

Used in general machine and installation applications
 Integrated rib provides axial strain relief
 Allows turning of the conduit, thus avoiding torsion stresses
 Pre-fixation on the conduit possible
 Allows solid fixation with 2 screws
 PA 6

Tube clamps

Type SGB & SGS

Type SGB - Tube clamp

	Order no. black	Fits to conduit size NW	Width (mm)	Fixing screws	PU (pcs)
	SGB-07	07	13.0	1 x M4	100
	SGB-09	10	13.0	1 x M4	100
	SGB-11	12	13.0	1 x M4	100
	SGB-16	17	16.0	1 x M5	100
	SGB-21	23	16.0	1 x M5	50
	SGB-29	29	19.0	1 x M6	30
	SGB-36	36	19.0	1 x M6	20
	SGB-48	48	19.0	1 x M6	20

For fixation of static conduits
Galvanized steel
Elastomer profile (EPDM) free from halogens
Smooth connection to PMA conduits
Good resistance to ozone and ageing
Temperature range: -40°C to +120°C

Type SGS - Tube clamp

	Order no. black	Fits to conduit size NW	Width x Height x Depth (mm)	Fixing screws	PU (pcs)
	SGS-36	36	80.0 x 48.0 x 19.0	2 x M6	20
	SGS-48	48	94.0 x 58.0 x 19.0	2 x M6	20
	SGS-56	56	118.0 x 72.0 x 24.0	2 x M8	10
	SGS-70	70	130.0 x 85.0 x 24.0	2 x M8	10
	SGS-95	95	156.0 x 110.0 x 24.0	2 x M8	10
	SGS-125	125	200.0 x 152.0 x 24.0	2 x M8	10

For fixation of static conduits
Galvanized steel
Elastomer profile (EPDM) free from halogens
Smooth connection to PMA conduits
Good resistance to ozone and ageing
Temperature range: -40°C to +120°C
Galvanized steel/EPDM

Alpha Contromatic Co., Ltd.

9 Soi On-nuch 62, Sukhumvit 77 Rd.
Suanluang, Suanluang, Bangkok 10250

Tel. 02 721 1801-8
M. 088 669 94

sales@alphac.co.th
www.alphac.co.th

